

DESCRIPTION

Rayston Tile Grout is a fine coloured powder which, when mixed with water, gives a smooth, easily applied creamy paste for clean grouting of ceramic tiles. It sets to a decorative water-resistant finish.

ADVANTAGES

- Water-resistant (suitable for swimming pools).
- Available in a range of colours.
- Resistant to cracking in joints up to 4 mm wide.
- Ideal for internal and exterior applications.
- Formulated for Middle East conditions

COMPOSITION

Rayston Tile Grout is a blend of hydrophobic cement, fillers and organic additives.

STANDARDS

BS 5980 - Cementitious Adhesives and Grouts ANSI 118.7 (Polymer Modified Cement Grouts)

APPLICATION PROCEDURES

- Allow at least 24 hours between fixing tiles and grouting.
- Mix grout powder with water to give a smooth, thick consistency.
- Gauging water for 5 kg is approx. 1.3 - 1.4 ltrs.
- Wait 15 minutes before using.
- Apply to tile joints with a squeegee, brush or sponge.
- Remove surplus grout with a damp sponge.
- When grouting is completed, polish tiles with a dry cloth.

WATCHPOINT

Certain types of tiles may stain when in contact with coloured cement grouts, it is therefore advisable to consult the tile manufacturer and carry out trials before use.

COVERAGE

1KG is sufficient for approximately 4 M2 using standard 15x15cm tiles.

STORAGE

Store out of direct sunlight, clear of the ground on pallets protected from rainfall. Avoid excessive compaction.

SAFETY PRECAUTIONS

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs (which may also be tainted with vapour until product is fully cured). Treat splashes to eyes and skin immediately. If accidentally ingested, seek immediate medical attention. Reseal containers after use.

PACKAGING

Rayston Tile Grout is available in 5 and 20 KG